



# Ti20-RBP

## Rechargeable NiMH Battery Pack

### *Safety Information*

The Ti20-RBP is a field-swappable, rechargeable Nickel Metal Hydride, 7.2 V, 1900 mAh battery.



A **Warning** identifies conditions and procedures that are dangerous to the user. A **Caution** identifies conditions and procedures that can cause damage to the Product or the equipment under test.

#### **Warning**

To avoid injury:

- Use the battery pack only as specified in the Fluke product-specific manual.
- Use only with compatible Fluke products
- Do not disassemble or short circuit the battery pack.
- Do not store the battery pack at temperatures >45 °C (113 °F) or operate for short durations >50 °C (122 °F).
- Do not incinerate or mutilate the battery pack.
- Must be recycled or disposed of properly
- Use only ac adapters approved by Fluke for the product to charge the battery or power the product.

#### **Symbols**

Symbol	Description
	Important information. See manual.
	This product complies with the WEEE Directive (2002/96/EC) marking requirements. The affixed label indicates that you must not discard this electrical/electronic product in domestic household waste. Product Category: With reference to the equipment types in the WEEE Directive Annex I, this product is classed as category 9 "Monitoring and Control Instrumentation" product. Do not dispose of this product as unsorted municipal waste. Go to Fluke's website for recycling information.

PN 4354709

May 2013

© 2013 Fluke Corporation. All rights reserved. All product names are trademarks of their respective companies. Specifications are subject to change without notice.

## ***Specifications***

Battery Type	NiMH, 7.2 V, 1900 mAh, 13.7 Whr
Dimensions	11 cm x 3 cm x 3 cm (4.3 in x 1.2 in x 1.2 in)
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Long Term Storage Temperature	-20 °C to 45 °C (-4 °F to 113 °F)